# ÖLFLEX® PLUG H05VV-F Net Connection Cable*

PVC net connection cable for electrical devices

ÖLFLEX® PLUG H05VV-F Net connecting cable, PVC, 1-2,5mm², 1.end angled earthing-type plug with double earthed contact/2.end IEC coupling or dismantled

## Info
Other colours and designs are available upon request



## Application range
Electrical devices

## Product features
For additional information regarding international plugs, please refer to our cable configurator at www.lappkabel.de
Apart from the cable related application restrictions to be paid attention to according to the application standard EN 50565-2 for this PVC cable H05VV-F, the fact that brighter outer sheath colours deviating from black significantly reduce the UV resistance of the outer sheath and, thus, the outdoor usability of the entire, finished cable at direct sun irradiation has to be respected, too

## Product Make-up
1st end: Gated, right-angled earthing-type plug with double earthing contact
2nd end: straight, 3-pin IEC coupling, moulded

## Technical Data

| | |
|---|---|
| Classification ETIM 5: | ETIM 5.0 Class-ID: EC001576<br>ETIM 5.0 Class-Description: Power cord |
| Classification ETIM 6: | ETIM 6.0 Class-ID: EC001576<br>ETIM 6.0 Class-Description: Power cord |
| Core identification code: | According to VDE 0293-308 (table T9) |
| Conductor stranding: | Fine wire according to VDE 0295 Class 5/ IEC 60228 Class 5 |
| Nominal voltage: | U0: 250 V AC |
| Test voltage: | 2000 V |

Last Update (23.01.2023)
©2023 Lapp Group - Technical changes reserved
Product Management www.lappkabel.de
You can find the current technical data in the corresponding data sheet.
PN 0456 / 02_03.16

# ÖLFLEX® PLUG H05VV-F Net Connection Cable*

| | |
|---|---|
| Protective conductor: | G = with GN-YE protective conductor |
| Temperature range: | 5 °C to 60 °C |

## Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
* Trade product, no Lapp product
Photographs and graphics are not to scale and do not represent detailed images of the respective products.
Prices are net prices without VAT and surcharges. Sale to business customers only.
Please observe the safety information as per DIN VDE 0620-1, Plugs and socket-outlets for household and similar purposes - Part 1: General requirements, appendix E: "Installation only by persons with the relevant electrotechnical expertise and experience!”


©2023 Lapp Group - Technical changes reserved

# ÖLFLEX® PLUG H05VV-F Net Connection Cable*

| Article number | Number of cores and mm² per conductor | Colour | Outer diameter [mm] | Length (m) | Copper index kg/1.000 pieces |
|---|---|---|---|---|---|
| 1st end: moulded right-angled earthing-type plug with double earthed contact<br>2nd end: straight, 3-pin C13 IEC coupling, moulded | | | | | |
| 73222334 | 3 G 1.0 | black | 6.3 - 8 | 2.5 | 72 |
| 73222336 | 3 G 1.0 | grey | 6.3 - 8 | 2.5 | 72 |
| 73222381 | 3 G 1.5 | grey | 7.4 - 9.4 | 5 | 216 |
| 73222335 | 3 G 1.0 | white | 6.3 - 8 | 2.5 | 72 |
| 2nd end: right-angled, 3-pin C13 IEC coupling, moulded | | | | | |
| 74320106 | 3 G 1.5 | black | 7.4 - 9.4 | 3.5 | 151.2 |
| 74320092 | 3 G 1.5 | black | 7.4 - 9.4 | 7.5 | 324 |
| 1st end: moulded right-angled earthing-type plug with double earthed contact<br>2nd end: 30 mm stripped, with conductor end sleeves | | | | | |
| 70261139 | 3 G 1.0 | black | 6.3 - 8 | 1.5 | 43.2 |
| 70261140 | 3 G 1.0 | black | 6.3 - 8 | 2 | 57.6 |
| 70261141 | 3 G 1.0 | black | 6.3 - 8 | 3 | 86.4 |
| 70261166 | 3 G 1.0 | black | 6.3 - 8 | 5 | 144 |
| 70261145 | 3 G 1.0 | grey | 6.3 - 8 | 1.5 | 43.2 |
| 70261146 | 3 G 1.0 | grey | 6.3 - 8 | 2 | 57.6 |
| 70261147 | 3 G 1.0 | grey | 6.3 - 8 | 3 | 86.4 |
| 70261143 | 3 G 1.0 | white | 6.3 - 8 | 2 | 57.6 |
| 70261144 | 3 G 1.0 | white | 6.3 - 8 | 3 | 86.4 |
| 70261148 | 3 G 1.5 | black | 7.4 - 9.4 | 1.5 | 64.5 |
| 70261149 | 3 G 1.5 | black | 7.4 - 9.4 | 2 | 86 |
| 70261150 | 3 G 1.5 | black | 7.4 - 9.4 | 3 | 129 |
| 70261160 | 3 G 1.5 | black | 7.4 - 9.4 | 5 | 215 |
| 70261185 | 3 G 1.5 | grey | 7.4 - 9.4 | 1 | 43.2 |
| 70261154 | 3 G 1.5 | grey | 7.4 - 9.4 | 1.5 | 64.5 |
| 70261155 | 3 G 1.5 | grey | 7.4 - 9.4 | 2 | 86 |
| 70261156 | 3 G 1.5 | grey | 7.4 - 9.4 | 3 | 129 |
| 70362272 | 3 G 1.5 | grey | 7.4 - 9.4 | 4 | 172 |
| 70261151 | 3 G 1.5 | white | 7.4 - 9.4 | 1.5 | 64.5 |
| 70261152 | 3 G 1.5 | white | 7.4 - 9.4 | 2 | 86 |
| 70261153 | 3 G 1.5 | white | 7.4 - 9.4 | 3 | 129 |
| 70261163 | 3 G 2.5 | black | 9.2 - 11.4 | 3 | 216 |

Last Update (23.01.2023)
©2023 Lapp Group - Technical changes reserved