

## 1m Black Straight Through DB9 RS232 Serial Cable - M/F

**Product ID:** MXT1001MBK



The MXT1001MBK Black Serial Extension Cable (1m) features one DB9 male connector and one DB9 female connector, providing a high quality extension for your RS232 serial devices, which enables you to position your peripheral devices as needed.

Note: This is a Straight-through cable, not a null-modem.

Expertly designed and constructed of top quality materials to ensure durability, this DB9 extension cable is backed by our Lifetime Warranty.

## Certifications, Reports and Compatibility

### Applications

- Extend RS232 serial connections by up to 1 meter

### Features

- **SERIAL EXTENSION CABLE:** DB9 Serial male to female cable allows you to extend the reach of your serial devices by up to 1 meter, reducing cable length restrictions and providing flexibility for positioning your serial devices as needed
- **QUALITY CONSTRUCTION:** High quality 28 AWG copper wires with Al-Mylar cable shielding and shielded metal shell connectors help prevent EMI interference; Molded PVC connectors with strain relief and PVC jacket prevent damage due to bends or rough usage
- **SCREW-ON STRAIGHT THROUGH CABLE:** This is Straight-through cable (not a null-modem cable) comes with thumbscrews for reliable tool-less installation and easy removal

- **LIFETIME SUPPORT:** Backed by StarTech.com lifetime warranty for dependable performance
- **SPECIFICATIONS:** 1m (3.3ft) DB9 serial Male to DB9 female Black 28AWG, 4.8mm OD Al-Mylar cable shield & Metal shell connectors Molded PVC strain relief & jacket Lifetime Warranty Note: This is a Straight-through cable, not a null-modem.

---

#### Prominence

|                               |                                                                     |
|-------------------------------|---------------------------------------------------------------------|
| Warranty                      | Lifetime                                                            |
| Description CDW 75 - 1st Line | StarTech.com 1m Black Straight Through DB9 RS232 Serial Cable - M/F |

---

#### Hardware

|                       |                                |
|-----------------------|--------------------------------|
| Connector Plating     | Nickel                         |
| Cable Jacket Material | PVC - Polyvinyl Chloride       |
| Cable Shield Material | Aluminum-Mylar Foil with Drain |

---

#### Connector(s)

|             |                     |
|-------------|---------------------|
| Connector A | DB-9 (9 pin, D-Sub) |
| Connector B | DB-9 (9 pin, D-Sub) |

---

#### Environmental

|                       |                           |
|-----------------------|---------------------------|
| Operating Temperature | 20C to 45C (68F to 131F)  |
| Storage Temperature   | -20C to 80C (-4F to 176F) |

---

#### Physical Characteristics

|                   |                    |
|-------------------|--------------------|
| Color             | Black              |
| Wire Gauge        | 28 AWG             |
| Cable Length      | 39.4 in [100 cm]   |
| Product Length    | 39.4 in [100.0 cm] |
| Product Width     | 1.3 in [33.0 mm]   |
| Product Height    | 0.6 in [15.0 mm]   |
| Weight of Product | 2.9 oz [81.0 g]    |

---

#### Packaging

## Information

|                              |                  |
|------------------------------|------------------|
| Package Quantity             | 1                |
| Package Length               | 8.9 in [22.5 cm] |
| Package Width                | 4.9 in [12.5 cm] |
| Package Height               | 0.0 in [0.1 mm]  |
| Shipping (Package)<br>Weight | 3.1 oz [87.0 g]  |

---

## What's in the Box

|                     |                                                  |
|---------------------|--------------------------------------------------|
| Included in Package | 1m Black Straight Through Serial Cable - DB9 M/F |
|---------------------|--------------------------------------------------|

---

***\*Product appearance and specifications are subject to change without notice.***

