

S12-100-/200-/110-



S12-100-230V



1-pole and 2-pole 16 A/250 V AC

Modular devices for DIN 60715 TH35 rail mounting with manual control and switch position indicator.

1 module = 18 mm wide, 55 mm deep.

100 % time on. Control power demand 5–6 W only.

Contacts 1 NO, 2 NO, 1 NO + 1 NC.

Contact gap 3 mm. Spacing of control connections/contact > 6 mm.

Devices for 25 A XS12, page 18-5.

Retrofittable auxiliary contact KM12, page 18-3.

The pin-compatible ES12DX-UC, ES12-200-UC and ES12-110-UC electronic impulse switches can also be used.

The universal control voltage UC covers the voltage ranges of 8 to 253 V AC at 50-60 Hz and 10 to 230 V DC.

Technical data page 18-7.

S12-100-12V	1 NO 16 A	EAN 4010312100455	23,20 €/pc.
S12-100-230V	1 NO 16 A	EAN 4010312100479	23,20 €/pc.
S12-100-8V, 24V, 12V DC, 24V DC	1 NO 16 A		25,10 €/pc.
S12-200-12V	2 NO 16 A	EAN 4010312100530	29,20 €/pc.
S12-200-230V	2 NO 16 A	EAN 4010312100554	29,20 €/pc.
S12-200-8V, 24V, 12V DC, 24V DC	2 NO 16 A		31,20 €/pc.
S12-110-12V	1 NO + 1 NC 16 A	EAN 4010312100493	29,20 €/pc.
S12-110-230V	1 NO + 1 NC 16 A	EAN 4010312100516	29,20 €/pc.
S12-110-8V, 24V, 12V DC, 24V DC	1 NO + 1 NC 16 A		31,20 €/pc.

Recommended retail prices excluding VAT.