



## 8 way satellite splitter

for the 8-fold distribution of Sat signals

| EAN           | Colour | Item no.  | Weight (Box) | Weight | Device (W x H x D)     | Box                     |
|---------------|--------|-----------|--------------|--------|------------------------|-------------------------|
| 4019588223103 | silver | 0022/3110 | 136 g        | 130 g  | 11.80 x 6.00 x 1.70 cm | 14.50 x 10.00 x 1.70 cm |

### TOP FEATURES

DC power pass

diode decoupled

DiSEqC-compatible

TECHNIROUTER-compatible

### DECOUPLING

5 - 862 MHz : Typ. 22 dB

950 - 1750 MHz : Typ. 22 dB

1750 - 2150 MHz : Typ. 21 dB

### RETURN LOSS

5 - 862 MHz : Typ. 9 dB

950 - 1750 MHz : Typ. 13 dB

1750 - 2150 MHz : Typ. 11 dB

### TECHNICAL DATA

Input : 1

Outputs : 8

Frequency range : 5 ... 2150 MHz

Shielding factor :  $\geq 75$  dB EN 50083-2 (Class A)

Connector type : F female

Impedance : 75  $\Omega$

### TRANSMISSION LOSS

5 - 862 MHz : Typ. 12 dB ( $\pm 1$ )

950 - 1750 MHz : Typ. 15 dB ( $\pm 1$ )

1750 - 2150 MHz : Typ. 18 dB ( $\pm 1$ )