

Product Data Sheet

Model identifier(s):	HL 3762					
Item	Symbol	Value	Unit		Item	Unit
Heat output					Type of heat input, for electric storage local space heaters only	
Nominal heat output	P_{nom}	2,0	kW		manual heat charge control, with integrated thermostat	N.A.
Minimum heat output (indicative)	P_{min}	1,0	kW		manual heat charge control with room and / or outdoor temperature feedback	N.A.
Maximum continuous heat output	$P_{max,c}$	2,0	kW		electronic heat charge control with room and / or outdoor temperature feedback	N.A.
Auxiliary electricity consumption					fan assisted heat output	N.A.
At nominal heat output	el_{max}	0,000	kW		Type of heat output / room temperature control	
At minimum heat output	el_{min}	0,000	kW		single stage heat output and no room temperature control	no
In standby mode	el_{SB}	0,000	W		Two or more manual stages, no room temperature control	no
					with mechanic thermostat room temperature control	yes
					with electronic room temperature control	no
					electronic room temperature control plus day timer	no
					electronic room temperature control plus week timer	no
					Other control options	
					room temperature control, with presence detection	no
					room temperature control, with open window detection	no
					with distance control option	no
					with adaptive start control	no
					with working time limitation	no
					with black bulb sensor	no
Contact details	Clatronic International GmbH, Industriering Ost 40, 47906 Kempen Germany					
N.A. = not applicable						