


KODAK K23A MAX SUPER Alkaline battery

Effective: 13/01/2021



Dimensions are in millimeters and include label.

Chemical system:

Alkaline, MnO₂ / KOH / Zn

Designations:

ANSI 1811A

Nominal Voltage:

12.0 V

Nominal Capacity:

33 mAh at 20 kOhms to 6.0 Volts

Weight:

7.5 g

Volume:

2.2 cm³

Recommended storage temperature:

10 – 25 °C, RH no more than 75%.

Operating temperatures:

-10 – 45 °C

Reaction:

$2\text{MnO}_2 + \text{Zn} + \text{H}_2\text{O} \rightarrow 2\text{MnOOH} + \text{ZnO}$

Terminals:

Flat contacts

Jacket:

Aluminium label

Note:

- 1) No added Mercury / 99.9999% Mercury Free
- 2) No added Lead /99.999% Lead Free
- 3) No added Cadmium / 99.9999% Cadmium Free
- 4) No added PFOS (Perfluorooctane sulfonates)
- 5) This battery complies with ANSI C18, IEC 60086, and EU Directive 2013/56/EU & 2006/122/EC.
- 6) SDS sheets are available on request from Strand Europe Ltd.

DANGER: Keep batteries out of reach of children. If swallowed, the battery can cause serious injury or death. Severe burns can occur within hours of ingestion. If you suspect that a battery has been ingested, seek immediate medical attention. Have doctor call CHEMTREC Day or Night on 1-800-424-9300 / +1 703-527-3887. **CAUTION:** Ensure that the battery compartment is completely secure, meaning closed and locked to prevent easy access by children. If the battery compartment cannot be completely secured, discontinue use of the product or keep out of sight and reach of children.



Brand Licensee

KODAK Batteries
KODAK LED Bulbs
KODAK Headphones
KODAK LED Flashlights

The Kodak trademark, logo and trade dress are used under license from Kodak.
© 2021 STRAND EUROPE LTD.
www.kodakbatteries.strandeurope.com

Page 1 of 1

Version: 2.2

Date: 13 January 2021