



Mini GBIC SFP transceiver LX Single-Mode (10km)



GVT-0301

H/W Version: 4

Product Overview

The LevelOne GVT-0301 SFP (Small form-factor pluggable) Transceiver provide flexibility for utilizing fiber Gigabit network connections in both data and telecommunication applications. GVT-0301 operates at a nominal wavelength of 1310nm and complies with Multi Source Agreement(MSA) Small Form Factor Pluggable(SFP) . It is a duplex LC transceiver designed for use in Gigabit Ethernet and to provide a IEEE-802.3z compliant link for 1.25Gb/s long reach applications up to 10KM

Support for Mini GBIC Connectivity

The GVT-0301 SFP Transceiver Series transceivers support LX standard optic with single-mode mini

GBIC connectors. They provide signal amplification to transfer and receive data between two ends of mini GBIC ports.

Multi-Purpose Usage

The GVT-0301 SFP transceivers can be used for distributed multiprocessing, switch-to-switch or converter-to-switch or converter-to converter interface, high-speed I/O file transfer, bus extension applications, and for a channel extender or data storage applications. The LevelOne GVT-0301 can be used in any LevelOne switch or modules that support SFP modules.



LC Connector

Key Features

- Small Form Factor Pluggable MSA compliant
- For Single Mode Applications
- Up to 1310nm & 1.25Gb/s
- Compliant for IEEE-802.3z Gigabit Ethernet
- Easy to install and Hot-pluggable
- Connect switches up to 10km away with each other
- Single 3.3V power supply
- Duplex LC Connector
- TTL signal detect indicator
- EEPROM with serial ID functionality

Works Well With



GSW-2453
3-slot Modularized Combo
Gigabit Switch



GVT-4000
10/100/1000Base-T to
1000Base-X Fiber Converter (SFP)

Technical Specifications

Standard Compliance
IEEE 802.3z
Data Rate Gigabit
1.25Gbd
Data Rate Fiber Channel
1.0625Gbd
Media
SMF
Optical Receiver Sensitivity
-20dBm
Optical Transmission Power
-9.5 ~ -3.0dBm
Power Budget
10.5dB
Center Wave Length
1310nm
Transmission Range
9/125um (up to 10km)

Connector
LC type
Supply Votage
3.1~3.5V
Max Voltage/Current
6V / 300mA
Temperature
0°C ~ 70°C
Humidity
5 ~ 90% (non-condensing)
Dimensions: (L x W x H)
55.5mm x 13.5mm x 8.5mm
Certifications
Class 1 Laser: EN60825-1
FDA 21: 1040.10, 1040.11

Application



Order Information

GVT-0301: Mini GBIC SFP transceiver LX Single-Mode (10km)

Package Contents

GVT-0301