
MPN: LVO231477

LC-SC Multimode fibre cable duplex 1m OM3 50/125 LSZH

The 50/125µm OM3 multimode bend insensitive fiber optic cable is less attenuation when bent or twisted compared with traditional optical fiber cables and this will make the installation and maintenance of the fiber optic cables more efficient. This 50/125 OM3 multimode fiber optic cable is ideal for connecting 10G SR, 10G LRM, SFP+ transceivers etc. for 10G/40G/100G Ethernet connections and is the preferred fiber specification for 10G Ethernet connections. The multimode patch cords are manufactured using LSZH cables which conform to IEC, EIA TIA or Telcordia standards.



- Designed for Data Centers, Industry and Computer Centers
- LSZH (Low Smoke Zero Halogen) and flame retardant
- Color: Aqua
- Length: 1 meter
- pre tested with test report
- Fibre Standard G.652.D

Specifications

Features	**Cable length**	1 m
	Cable type	Duplex
	Certification	IEC, EIA, TIA, Telcordia
	Cladding diameter	125 µm
	Connector 1	LC/UPC
	Connector 1 gender	Male
	Connector 2	SC/UPC
	Connector 2 gender	Male
	Core diameter	50 µm
	Ethernet interface type	10 Gigabit Ethernet, 40 Gigabit Ethernet, 100 Gigabit Ethernet
	Fiber mode structure	Multi-mode
	Fibre optic type	OM3
	Full duplex	Yes
	Halogen-free	Yes
	Jacket material	Low smoke zero halogen (LSZH)
	Product colour	Aqua colour
Legal Information	**ADR Information**	No restrictions
	Country of Origin	China
	Tariff No.	8544700099
	UNSPSC Code	26121607
Other features	**Connector(s)**	LC - SC
Package dimensions	**Gross Weight (Package, kg)**	0.022 kg
Packaging data	**Quantity**	1

Packaging data	**Quantity per pack**	1 pc(s)
Product dimensions	**Net Weight (Product, kg)**	0.02 kg
Technical details	**Doesn't contain**	Halogen
Vendor information	**Brand Name**	Lanview
	Warranty	5 Year(s)
Weight & dimensions	**Cable diameter**	2 mm

Other products in this series

Cable length	
1	LVO231477
2	LVO231303
3	LVO231478
5	LVO231479
10	LVO231480

Other images

