

A SMART, A4 COLOUR SINGLE FUNCTION DEVICE WITH INTEGRATED WI-FI AND SECURE PRINT



i-SENSYS LBP722Cdw

User-friendly A4 colour single-function printer suitable for small-medium sized businesses with a high print output.



38 PPM
Print speed



HIGH PRODUCTIVITY
Automatic double-sided printing



2,300 SHEETS
Maximum capacity with additional cassettes



WIRELESS CONNECTIVITY
Print from smart phones and tablets, thanks to Wi-Fi and NFC connectivity

Enhanced connectivity

Embrace flexible working with a variety of connectivity features, including Wi-Fi support, NFC and Universal Print by Microsoft.

Boosted productivity

Maximise your print output with rapid print speeds and an expandable paper capacity of up to 2,300 sheets with additional cassettes.

Enhanced security

Have confidence in your data security with Secure Print and advanced integrated security software, such as McAfee Embedded Control and TLS1.3 security layer.

Exceptional image quality

Achieve superior colour graphics, images and texts with laser-quality printing for professional-level documents.

Improved serviceability

Simple installation, easy maintenance and excellent durability enable minimal downtime and reduced service costs.

Canon

TECHNICAL SPECIFICATIONS

PRINTER ENGINE

Print speed	Single sided (A4): Up to 38 ppm colour and mono Double sided (A4): Up to 38 ipm colour and mono Single sided (A5-Landscape): Up to 59 ppm colour and mono
Printing method	Colour laser beam printing
Print quality	Up to 1200 x 1200 dpi
Warm-up time	Print ready message shown: Approx. 2 seconds or less from power on
First Page Out Time	Colour: approx. 6.3 seconds Mono; approx. 5.3 seconds
Recommended Monthly Print Volume	2,000 - 7,500 pages per month
Duty cycle	Max. 80,000 pages per month¹
Print margins	4 mm-top, bottom, left and right
Advanced printing features	Secure Print Print from USB memory key (JPEG/TIFF/PDF/XPS) Barcode Print² Touch & Print (NFC) iOS: AirPrint, Canon PRINT Business app Android; Mopria certified, Canon Print Service Plug-in, Canon PRINT Business app Microsoft Universal Print

MEDIA HANDLING

Paper input (Standard)	550-sheet cassette 100-sheet multi-purpose tray
Paper input (Option)	550-sheet cassette x 3 (Paper Feeder PF-D1) 550-sheet cassette (Cassette Feeding Unit-AV1)
Maximum paper input capacity	Up to 2,300 sheets
Paper output	200-sheet face down
Media types	Multi-Purpose Tray: Plain paper, Recycled paper, Heavy Paper, Thin paper, Colour paper, Coated paper, Pre-punched, Post card, Envelope Cassette: Plain paper, Recycled paper, Heavy Paper, Thin paper, Label, Colour paper, Coated paper, Pre-punched
Media sizes	Cassette (Standard): A4, A5, A5 (Landscape), A6, B5, Letter, Executive, Statement, GLTR, 16K, Custom sizes: Min. 101.6 x 148 mm Max. 216.0 x 297 mm. Multi-purpose tray: A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, 16K, Post card, Envelop (COM10, Monarch, C5, DL), Custom sizes: Min. 76.2 x 127 mm Max. 216.0 x 355.6 mm. Cassette (Optional): A4, A5, A5 (Landscape), A6, B5, Legal, Letter, Executive, Statement, GLTR, ILGL, GLGL, Foolscap, F4A, 16K, Custom sizes: Min. 101.6 x 148 mm Max. 216.0 x 355.6 mm
Media weights	Cassette (standard and optional): 60 to 163 g/m² Multi-purpose tray: 60 to 216 g/m²
Double sided printing	Automatic Cassette: A4, A5, B5, Legal, Letter, Executive, OFFICIO, B-OFFICIO, M-OFFICIO, GLTR, ILGL, GLGL, Foolscap, F4A, 16K Custom size - Min. 148 x 210 mm Max. 216 x 355.6 mm 60 to 163 g/m²

GENERAL FEATURES

Power requirements	220-240V (±10%) 50/60Hz (±2Hz)
Power consumption	Maximum: Approx. 1500W or less Active: Approx. 729W or less Standby: Approx. 34.4W or less Sleep: Approx. 1.1W or less Typical Electricity Consumption (TEC): 0.45kWh/week ⁹ For detailed information relating to Lot26 regulation, please go to: http://www.canon-europe.com/For_Work/Lot26/index.aspx
Noise level	Sound power³ Active: Simplex 65 dB or less (BW) / 66 dB or less (CL) Duplex 67 dB or less (BW) / 68 dB or less (CL) Standby: 48 dB or less Sound pressure³ Active: Simplex 50 dB or less (BW) / 51 dB or less (CL) Duplex 52 dB or less (BW) / 52 dB or less (CL) Standby: 33 dB or less 458 mm x 464 mm x 388 mm Approx. 29 kg Temperature: 10 to 30°C (50 to 86°F) Humidity 20 to 80% RH (no condensation)
Dimensions (W x D x H)	
Weight	
Operating environment	
Control panel	5 Line LCD, 5 LED (Online, Ready, Message, Job and Energy saver), Buttons, 10-key numeric keypad

CONTROLLER

Processor Speed	1GHz x 2
Memory	2GB
Storage	32GB eMMC (available space 15GB)
Printer Languages	UFR II (Ultra Fast Rendering), PCL5c⁴, PCL6, Adobe® PostScript3
Fonts	93 PCL fonts (93 Roman, 10 Bitmap fonts, 2 OCR fonts) Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese)*5 Barcode Fonts*2 136 PostScript fonts
Interface and connectivity	USB 2.0 High-Speed, 10BASE-T/100 BASE-TX/1000BASE-T Wireless 802.11b/g/n, Wireless Direct Connection
Network Protocol	Print: TCP/IP (LPD/Port9100/IPP/IPPS/FTP/WSD)

Management:	SNMPv1, SNMPv3 (IPv4,IPv6)
Security:	Security: TLS1.3, IPSec, IP/Mac address filtering, IEEE802.1X, SNMPv3, SSL (HTTPS, IPPS), Dual Network Support Security (wireless): Infrastructure Mode: WEP(64/128 bit), WPA-PSK(TKIP/AES), WPA2-PSK(TKIP/AES), WPA-EAP (AES), WPA2-EAP (AES) Access Point Mode: WPA2-PSK(AES) Wi-Fi Direct Mode: WPA2-PSK (AES) Remote User Interface (RUI), Department ID Management, Toner Status Tool, iW Enterprise Management Console: Server-based software for centralised management of a fleet of devices eMaintenance: embedded RDS allows remote eMaintenance services such as meter capture, automatic consumables management and remote diagnostics. Content Delivery System: Server platform enables automatic firmware update to the device.
Operating Systems Compatibility	Windows® 10 / Windows® 8.1 / Server® 2019 / Server® 2016 / Server® 2012R2 / Server® 2012 / Mac OS X version 10.11 & up Linux®/Citrix

CONSUMABLES All-in-One cartridges

Standard:	Cartridge 064 Black (6,000 pages*)⁸ Cartridge 064 Cyan (5,000 pages*)⁸ Cartridge 064 Magenta (5,000 pages*)⁸ Cartridge 064 Yellow (5,000 pages*)⁸ High yield: Cartridge 064H Black (13,400 pages*)⁸ Cartridge 064H Cyan (10,400 pages*)⁸ Cartridge 064H Magenta (10,400 pages*)⁸ Cartridge 064H Yellow (10,400 pages*)⁸
-----------	---

ACCESSORIES/OPTIONS Items

	Paper Feeder PF-D1 (550-sheet cassette) x 3 CST.Feeding Unit-AV1 (550-sheet cassette pedestal) Barcode Printing Kit-D1 (Enables barcode printing capability) PCL Font Set-A1 (Enables Unicode printing capability on SAP and supports Andale font) Plain Pedestal-P2 Plain Pedestal-AA1 Waste Toner Box WT-B1
--	---

Notes

[1] Duty cycle is defined as the maximum number of printed pages for a single peak month. Any usage above the recommended duty cycle may decrease the life of the product

[2] Accessory - Barcode Printing Kit-D1 - is required

[3] Declared noise emission in accordance with ISO 9296

[4] Commands supported only. Third party driver or direct printing from application required.

[6] Web distribution only. Driver will be available in H2 2021

[7] Based on ISO/IEC 19798

[8] Printer ships with Black: 6,000 pages, C/M/Y: 3,200 pages starter cartridges

[9] As per US ENERGY STAR® version3.0.



A SMART, A4 COLOUR SINGLE FUNCTION DEVICE WITH INTEGRATED WI-FI AND SECURE PRINT

User-friendly A4 colour single-function printer suitable for small-medium sized businesses with a high print output.



PRODUCT DETAILS:

PRODUCT NAME	Mercury Code	EAN Code
i-SENSYS LBP722Cdw EU SFP	4929C006AA	4549292181814

ACCESSORIES:

PRODUCT NAME	Mercury Code	EAN Code
Paper Feeder PF-D1	0942C001AA	4549292050714
Cassette Feeding Unit-AV1	4997C001AA	4549292182989
PCL FONT SET-A1E	4821B003AA	-
Barcode Printing Kit-D1E	3999B005AA	-
Plain Pedestal Type-P2	1632C002AA	8714574668635
Plain Pedestal Type-AA1	5512C002AA	8714574668666
Waste Toner Box WT-B1	0942C002AA	4549292052688



A SMART, A4 COLOUR SINGLE FUNCTION DEVICE WITH INTEGRATED WI-FI AND SECURE PRINT

User-friendly A4 colour single-function printer suitable for small-medium sized businesses with a high print output.



CONSUMABLES

PRODUCT NAME	Mercury Code	EAN Code
Cartridge 064 Yellow	4931C001AA	4549292182491
Cartridge 064 Magenta	4933C001AA	4549292182514
Cartridge 064 Cyan	4935C001AA	4549292182538
Cartridge 064 Black	4937C001AA	4549292182552
Cartridge 064H Yellow	4932C001AA	4549292182507
Cartridge 064H Magenta	4934C001AA	4549292182521
Cartridge 064H Cyan	4936C001AA	4549292182545
Cartridge 064H Black	4938C001AA	4549292182569

