



Specifications

- * Line length: 0.5-3 meters
- * Gauge:
- 28 AWG (7/0.12TS) signal cable * 2C (white/green) + 24 AWG (11/0.16TS) power cable * 2C (red/black) + AL + D (7/0.12BC) + B (64*0.12AM) 3-meter line with additional single magnetic ring / 5-meter line with additional dual magnetic ring
- * Diameter OD:4.5mm
- * The wire is coated with PVC.
- * Wire core material: tin-plated copper
- * Shielding Aluminum Foil + Woven
- * cores: 4 cores + 1 floor
- * Carrying Current: /
- * pin for USB-A: 4-pin
- USB2.0 A/F Black Vinyl Core (94V-0) Terminal Gold-plated G/F Nickel-plated Iron Case Welded Plug with AF Housing
- USB2.0 A/M Black Vinyl Core (94V-0) Terminal Gold-Coated G/F, Nickel-Coated Iron Case, Short Body Welded Plug
- * Insertions and withdrawals: 3000 times
- * Swing cycles: 1000 times (with a lifting capacity of 200G, a 60-degree angle, and a frequency of 40 times per minute)
- * Interface Version/Data Transfer :USB 2.0/480 Mbps
- * Flame Retardant Grade: VW-1
- * Operating Temperature/Storage Temperature: 0~45°C / -15~70°C
- * Environmental requirements comply with EU RoHS 2.0, REACH, SVHC, Appendix 17, POPs; California 65, TSCA; and China RoHS.