


DIGITUS Cat.6 F/UTP installation cable, 100 m, simplex, Dca

DK-1624-VH-1
EAN 4016032441984



CAT 6 F-UTP installation cable, 250 MHz Dca (EN 50575), AWG 23/1, 100 m paper box,

The Digitus Cat 6 F/UTP installation cable is designed for use in the structured data center and the building cabling according to ISO/IEC 11801, DIN EN 50288-5-1, DIN EN 50173, IEC 60332-1. The cable is perfectly suitable for the transmission of both analog and digital data and also supports POE and POE+.

Future-oriented standards and high-end quality for your network.

- Physical properties:
 - Conductor: Bare annealed copper, solid AWG 23/1
 - System/s of AVCP: AVCP 3
 - Insulation: HD-PE (High Density Polyethylene)
 - Total number of insulated conductors: 8, twisted in 4 pairs
 - Color code: Blue-white, orange-white, green-white, brown-white
 - Individual pair shield: None
 - Overall shielding: Aluminum foil, providing 100% coverage, drain wire
 - Outer sheath: Eca to B2ca acc. to EN 50575; LSZH
 - Outer sheath diameter (nominal): 0.5 mm (Eca); 0,6 mm (Dca); 0,8 mm (Cca); 0,08 mm (B2ca)
 - Outer sheath color: Purple
- Mechanical properties:
 - Tensile loading: 150N max.
 - Dynamic bending radius: 8x AD mm min.
 - Static bending radius: 4x AD mm min.
- Shipping- and storage temperature range: -20 °C up to +60 °C
- Operating temperature range: -20 °C up to +75 °C






- Installation temperature range: 0 °C up to +50 °C
- Overall diameter Simplex (nominal): 7.0 (Eca); 7,2 mm (Dca); 7,6 mm (Cca); 7,6 mm (B2ca)
- Weight (kg/km): 46 kg (Eca); 47 kg (Dca); 48,5 kg (Cca); 48,5 kg (B2ca)
- Electrical properties:
 - Impedance: 100±5 Ohm @ 1-250 MHz
 - Capacitance: 45 pF/m nominal @ 800 Hz
 - Capacitance unbalance (pair-ground): 1.5 pF/m max. @ 1 KHz
 - Insulation resistance: 5 GOhm x km min.
 - DC loop resistance: 147 Ohm/km max. (2% max. resistance unbalance)
 - Voltage resistance: 72 Vdc max.
 - Coupling attenuation: 40 dB
 - Signal propagation delay: 535 nS/100 m max.
 - Propagation delay: 20 nS/100 m max.
 - Separating class: „c“ acc. to EN 50174-2
 - NVP: 69%

Attributes

- Assortment: Twisted Pair Installation Cables
- Category: CAT 6
- Shielding: F-UTP, foil shielding
- CPR: Dca
- Length: 100 m
- Color: violet
- Jacket: LSOH
- Structure: 4 x 2 AWG 23/1, solid twisted pair

Logistics						
	Number (pcs)	Weight (kg)	Depth (cm)	Width (cm)	Height (cm)	cm³
Packaging Unit Carton	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Inside	1	0.00	0.00	0.00	0.00	0.00
Packaging Unit Single	1	0.00	0.00	0.00	0.00	0.00
Net single without Packaging	1	0.00	0.00	0.00	0.00	0.00

More images:



Safety notes

- Data cables must not be bent, stretched or twisted excessively. Sharp bends can damage the cable sheath and lead to failures or short circuits.
- Installation only by trained specialists.
- Installation only in dry rooms.
- The data cable must not be in direct contact with other electrical cables or high-voltage sources in order to avoid electromagnetic interference.

EU responsible person

EU based economic operator ensuring the product complies with the required regulations.

ASSMANN Electronic GmbH
Auf dem Schüffel 3
Lüdenscheld, Germany
<https://www.assmann.com>
info@assmann.com