



Lexmark XM1342

Productivity. Reliability. Security.



Lexmark XM1342

Light, compact, and fast, the XM1342 multifunction supports output up to 40 pages per minute*, plus double-side automatic scanning, copying, faxing and touch-screen convenience. Connect via Wi-Fi, USB or Ethernet and add an optional 550-sheet paper tray or available Extra High Yield Unison™ toner offering up to 18,000 pages of output**.

Compact monochrome versatility

- ▶ Get monochrome output at up to 40 pages per minute*, with a first page as fast as 5.9 seconds.
- ▶ Capture documents with double-side automatic scanning at up to 92 A4-size images per minute.
- ▶ Tackle your workload with the power of a 1-GHz dual-core processor and 512 MB of memory.
- ▶ Compact dimensions of 339 mm high x 411 mm wide x 366 mm deep help it fit almost anywhere.



Connect and command

- ▶ Connect via Wi-Fi, Ethernet and USB.
- ▶ Simplify mobile printing via Lexmark Mobile Print app, as well as Mopria® and AirPrint technologies.
- ▶ Take command of printing, copying, faxing, and automatic two-sided scanning with a 7.2 cm colour touch screen.
- ▶ Built-in cloud connectors help you save scans to and retrieve files from popular cloud services Box, DropBox, Google Drive, and Microsoft OneDrive.

Sustained output, enduring quality

- ▶ Available Unison™ toner provides up to 18,000 pages** of output sheets for more printing and less downtime.
- ▶ Optional paper tray increases total input capacity to 900 sheets to support longer print runs and enhanced media flexibility.
- ▶ Steel frame and lifetime imaging components mean long life and minimal maintenance.

Robust, built-in security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe—in the document, on the device, over the network, and everywhere in between.
- ▶ A range of embedded features harden the device against attacks.
- ▶ Standard Confidential Print feature helps ensure output security via simple PIN.

Save paper, save energy

- ▶ Automatic two-sided printing is standard.
- ▶ Built-in energy-saving modes help support ratings of EPEAT® Silver and ENERGY STAR® certified.
- ▶ The Lexmark Cartridge Collection Programme (LCCP) and Lexmark Equipment Collection Programme (LECP) minimise waste and support recycling (availability varies by country).

* Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: www.lexmark.com/ISOspeeds.

** Average yield based on approximately 5% print coverage.

Lexmark XM1342



P/N
29S0490

Hardware
Lexmark XM1342

P/N
29S0600

Papirhåndtering
Papirmagasin til 550 ark

P/N
1021294
SPD0002

Tilslutning
USB-kabel (3 m.)
Overspændingsbeskytterenhed,
220-240V

P/N
3073173
35S8502

Furniture
Drejekabinet
Justerbart stativ

- 1 **Multifunction product with 7.2 cm touch screen**
339 x 411 x 366 mm
- 2 **100-Sheet multipurpose feeder**
Inkluderede dimensioner er en del af basismodellen
- 3 **250-Sheet tray**
Inkluderede dimensioner er en del af basismodellen

- 4 **Papirmagasin til 550 ark**
107 x 370 x 378 mm

 Standard
 Valgfrit

Supports one optional 550-sheet tray.

All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at http://www.lexmark.com/publications/furniture_safety/

Produktspecifikationer		Lexmark XM1342
Udskrivning		
Display	2.8 inch (7.2 cm) LCD touch panel	
Udskriftshastighed	Op til: Sort: 40 sider/min ¹ (A4)	
Tid indtil første side	Sort: 5.9 sekunder	
Printopløsning	Sort: 2400 billedkvalitet, 300 x 300 dpi, 1200 x 600 dpi, 600 x 600 dpi	
Hukommelse / Hukommelse i netværksmodel	Standard: 512 MB / Maksimum: 512 MB	
Harddisk	Ikke tilgængeligt	
Anbefalet volumen pr. måned	800 - 8000 Sider ²	
Maks. månedlig belastning	Op til: Duty Cycle: 80000 sider/måned ³	
Kopiering		
Kopieringshastighed	Op til: Sort: 39 sider/min. ¹ (A4)	
Tid indtil første kopi	Sort: 5.9 sekunder	
Scanning		
Scanner type / ADF Scan	Flatbed scanner med ADF / DADF (single pass Duplex)	
A4/Letter Dupleks scanningshastighed	Op til: Sort: 92 / 96 sider/ min. / Farve: 40 / 42 sider/ min.	
A4/Letter Scanningshastighed	Op til: Sort: 46 / 48 sider/ min. / Farve: 20 / 21 sider/ min.	
Kopier/Fax/Scan	Op til: Papirinput kapacitet: 50 sider med 20 lb eller 75 g/m ² tykt papir (ADF)	
Faxning		
Modemhastighed	ITU T.30, V.34 Half-Duplex, 33.6 Kbps	
Tilbehør ⁴		
Ydelse for tonerkassetter	op til: 18,000 ⁵ -page High Yield Cartridge	
Anslået ydelse for billedenhed	op til: 40000 sider, baseret på 3 gennemsnitlige A4-sider pr. udskriftsjob og ~ 5% dækning ⁶	
Kassette(r) leveres med produkt	3.000 ⁵ siders sort Return Program tonerkassette (starter)	
Papirhåndtering		
Papirhåndtering	Standard: 100-arks multifunktionsføder, Integreret Duplex, Udskriftsbakke til 150 ark, Integreret papirmagasin til 250 ark	
Papirhåndtering	Ekstra tilbehør: 550-arks skuffe	
Papirinput kapacitet	Op til: Standard: 350 sider med 20 lb eller 75 g/m ² tykt papir / Maksimum: 900 sider med 20 lb eller 75 g/m ² tykt papir	
Papiroutput kapacitet	Op til: Standard: 150 sider med 20 lb eller 75 g/m ² tykt papir / Maksimum: 150 sider med 20 lb eller 75 g/m ² tykt papir	
Understøttede medietyper	Papiretiketter, Card Stock, Almindeligt papir, Kuverter, Refer to the Paper & Specialty Media Guide	
Understøttede mediestørrelser	A6, Oficio, 7 3/4 konvolut, 9 konvolut, JIS-B5, A4, Legal, A5, Brev, Udmelding, Executive, Universel, DL konvolut, Folio, 10 konvolut	
Generelt ⁷		
Standard tilslutning	USB kompatibel med USB 2.0 specifikationer (Type B), Ethernet 10/100BaseTX (RJ-45)	
Lydniveau ved i brug	53 dBA (Udskrivning) / 59 dBA (Kopiering) / 58 dBA (Scanning)	
Påkrævet driftsmiljø	Fugtighed: 8 til 80% Relativ fugtighed / Temperatur: 10 til 32 ° C (50 til 90 ° F) / Højde: 0 - 2896 meter (9500 fødder)	
Størrelse / Vægt	H x B x D: 339 x 411 x 366 mm / 12.8 kg	
ENERGY STAR Typical Electricity Consumption	TEC: 0.54 kilowatt-hours per week	

Alle oplysningerne kan ændres uden varsel. Lexmark er ikke ansvarlig for eventuelle fejl eller udeladelser.

¹ Udskrivnings- og kopieringshastigheder målt i henhold til henholdsvis ISO / IEC 24734 og ISO / IEC 24735 (ESAT). For mere information se: www.lexmark.com/ISOspeeds.

² "Anbefalet månedlig sidevolumen" er en række sider, der hjælper kunder med at evaluere Lexmarks produkttilbud baseret på det gennemsnitlige antal sider, som kunderne planlægger at udskrive på enheden hver måned. Lexmark anbefaler, at antallet af sider pr. Måned ligger inden for det angivne område for optimal enhedens ydeevne, baseret på faktorer, herunder: leveringsintervaller, papirindlæsningsintervaller, hastighed og typisk brug af kunder. ³ "Maksimal månedlig arbejds cyklus" defineres som det maksimale antal sider en enhed kan levere i en måned ved hjælp af en multishift-operation. Denne beregning giver en sammenligning af robusthed i forhold til andre Lexmark-printere og multifunktionsmaskiner. ⁴ Produktfunktioner kun med udskiftningspatroner designet til brug i en bestemt geografisk region. Se www.lexmark.com/regions for flere detaljer.

⁵ Gennemsnits-yield ved cirka 5 % udskriftsdækning pr. farve. ⁶ Faktisk ydelse kan variere afhængigt af andre faktorer såsom enhedshastighed, papirstørrelse og papirretning, tonerdækning, bakke kilde, procentdel af sort-only-udskrivning og gennemsnitlig udskrivningsjobkompleksitet. ⁷ Printere sælges under visse licens / aftaleforhold. Se www.lexmark.com/printerlicense for detaljer.

© 2021 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries.

Apple and AirPrint are trademarks of Apple Inc., registered in the U.S. and other countries. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are registered trademarks and service marks of Mopria Alliance, Inc. in the United States and other countries. Unauthorised use is strictly prohibited. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. EPEAT® is a trademark of the Green Electronics Council in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).

