



Toslink Digital Optical Audio Cable

2 x Toslink S/PDIF Male, 3 m (10 ft.), Gold-plated Contacts, Black

Part No.: [356084](#)

EAN-13: 0766623356084 | UPC: 766623356084

Toslink Cable - SPDIF digital optical audio cable, male to male (M/M), with premium HiFi quality for brilliant sound in your home theater

Get the ultimate sound experience for your home entertainment with the professional-grade Manhattan Toslink Digital Optical S/PDIF Audio Cable. It transmits superior high-definition surround sound between AV components with fiber-optic interfaces. Rediscover your favorite movies, music and video games with crystal-clear audio. This optical audio cable is ideal for all devices with an optical interface such as AV receivers, (pre)amps, soundbars, sound systems, TVs, PCs, DACs (digital-to-analog converters), PlayStation[®] (PS3/PS4/PS4 Pro), Xbox[®] (One/360) and more.

State-of-the-art transmission technology plus gold-plated contacts

The cable's high-grade optical fiber and polished lens allow for the best possible performance without compromising sound quality. Its construction from fiber strands makes it completely immune to electromagnetic interference (EMI) and radio frequency interference (RFI) that lower-quality HDMI cables can suffer from. Gold-plated contacts keep your connections always corrosion-free.

Features:

- Two male Toslink S/PDIF plugs to connect a media source to an audio device
- Premium HiFi quality with lossless, distortion-free fiber optics
- Ideal for all devices with an optical interface such as AV receivers, (pre)amps, soundbars, sound systems, TVs, PCs, DACs, PlayStation® (PS3/PS4/PS4 Pro), Xbox® (One/360), and more
- Gold-plated contacts for corrosion-free connections
- Immunity to EMI and RFI
- Compatible with all S/PDIF In/Out and OPT In/Out ports
- Flexible, durable jacket with heavy-duty strain relief
- Plug and play; requires no external power supply
- Lifetime warranty

Specifications:

Standards and Certifications

- CE
- RoHS
- REACH
- WEEE

General

- Two Toslink (S/PDIF, optical) males
- Gold-plated contacts
- PVC boot with strain relief
- Optical fiber
- PVC jacket
- Length: 3 m (10 ft.)
- Outer diameter (OD) jacket : 2.2 mm (0.09 in.)
- Outer diameter (OD) fiber: 1 mm (0.04 in.)
- Bend radius: 20 mm
- Fiber pulling/tensile strength: 25 kg (250 N)
- Weight: 20 g (0.71 oz.)

Operating Environment

- Operation temperature: 0 - 50°C (32 - 122°F)
- Storage temperature: -20 - 70°C (-4 - 158°F)

Package Contents

- Toslink Digital Optical S/PDIF Audio Cable

This product is also available in other lengths by the model number shown:

- #356060 - 1 m (3 ft.)
- #356077 - 2 m (7 ft.)
- #356091 - 5 m (14 ft.)

Note: Before installing this cable, remove the protective dust cap on each connector.



