

AXIS TW1201 Body Worn Mini Cube Sensor

The wearable camera for everyone

AXIS TW1201 Body Worn Mini Cube Sensor is designed to be extremely discreet and to offer flexible positioning for recording. Its small size, low weight and an easy-to-move magnet mount make it suitable for wearing on lightweight material like the lapel of a blazer, or even a t-shirt. AXIS TW1201 provides the same optical performance as AXIS W100, delivering sharp images even in challenging conditions. It comes in both white and black.

- > **Extremely discreet**
- > **Lightweight**
- > **Same optical performance as AXIS W100**
- > **Flexible magnet mount**
- > **For use with AXIS W100**



AXIS TW1201 Body Worn Mini Cube Sensor

Camera		Mounting	Magnetic
Image sensor	1/2.9" progressive scan RGB CMOS Sensitivity: 0.1 lux	Operating conditions	-20 °C to 55 °C (-4 °F to 131 °F) Humidity 0–95% RH (non-condensing)
Lens	Focal length, 2.1 mm Horizontal field of view: 141.4° Vertical field of view: 82° Fixed iris, F2.1	Storage conditions	-40 °C to 65 °C (-40 °F to 149 °F) Humidity 10–90% RH (non-condensing)
Shutter speed	1/32000 s to 1/25 s with 50 Hz 1/32000 s to 1/30 s with 60 Hz	Approvals	EMC EN 55032 Class B, EN 55035, FCC Part 15 Subpart B Class B, ICES-3(B)/NMB-3(B), RCM AS/NZS CISPR 32 Class B Safety IEC/EN/UL 62368-1, CAN/CSA C22.2 No. 62368-1 Environment IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-14, IEC 60068-2-78, IEC/EN 60529 IP54
Video		Dimensions	45 x 45 x 23 mm (1.8 x 1.8 x 0.9 in) Cable length: 0.8 m (2.6 ft)
Video compression	H.264 (MPEG-4 Part 10/AVC) High Profile (with AXIS W100)	Weight	Camera: 40 g (0.09 lb) Camera mount: 13 g (0.03 lb)
Resolution	1920x1080, 1280x720	Included accessories	AXIS TW1905 Mini Cube Magnet Mount
Frame rate	25 fps at 50 Hz 30 fps at 60 Hz	Optional accessories	AXIS TW1901 Cable Holder For more accessories, see axis.com
Wide dynamic range	WDR (with AXIS W100)	Warranty	3-year warranty, see axis.com/warranty
Video streaming	Axis Zipstream for body worn (with AXIS W100)	Environmental responsibility:	
General		axis.com/environmental-responsibility	
Casing	IP54-rated Plastic casing Color: black NCS S 9000-N, or white NCS S 1002-B		
Sustainability	PVC free, BFR/CFR free		
Connectors	USB		