

MS838B

2.4G Wireless 2D Imager Scanner





100 M Connection | Keeps data even out of range | 16 hours operation time

Delivering reliable performance and affordable price, the MS838B wireless 2D imager scanner combines superior 1D and 2D barcode scanning with the freedom of wireless technology. The well-integrated mobility design allows users to move around without being restricted, while supporting high comfort over long periods of operation. This cost-effective and reliable handheld scanner provides the optimum combination of performance that makes it an ideal scanning tool for a wide range of market applications, such as point-of-sale, personal data identification and inventory control.

Move without Restrictions

Design for mobile workers, the MS838B comes with a USB dongle that enables users to capture barcodes with freedom wireless connection. Easy plug-and-play function, the MS838B pairs easily to laptops or PCs without complicated set-up. Besides, it allows users to transmit data to the host from up to 100 meters from the base via 2.4G wireless communication. When it is out of range, the MS838B barcode scanner can store 40,000 EAN codes in memory and upload them to your devices at your own convenience. It allows associates to capture barcodes from the checkout counter or checking your store's inventory in the retail store without restrictions.

Reliable 2D Scanning Performance

Quickly and accurate capturing most 1D and 2D barcodes or coupon displayed on the phone, the MS838B helps retail cashier to checkout without any frustration. It delivers great performance up to 60 fps per second as well as capturing high density with a 4 mil resolution and a scanning width up to 180mm. It is suitable to streamline everyday processes in supermarket, retail store and warehouse applications.

Durable

Furthermore, it has an IP54 rating for dust and water resistance as well as a 1.5 meter drop spec that provides superior durability and reliability. Combining high performance and compact design, M838B gives mobile worker conveniently and safely while on the go.

Features

- 2.4G wireless transmission range up to 100m in the line of open sight.
- Reads all major 1D and 2D barcodes including printed and digital
- Long battery life up to 16 hours per a fully charged battery
- Plug and play, convenient to use
- Durable, Compact and Long life trigger design
- Rugged design by IP54 and 1.5m drops
- Buffer mode for out-of-range reading
- Instant decoding feedback: LED, Buzzer indicators

unitech
because we care

unitech
because we care

MS838B
Specifications



Optical & Performance

Sensor	CMOS Sensor,640 x 480 pixels
Aiming Element	25 nm LED
Illumination	Color temperature 3500 k
Ambient Light	0-10000 Lux
Scan Rate	60 fps/s
Skew Angle	±65°
Pitch Angle Sensor	±65°
Roll Angle	360°
Memory	16MB
Optical Resolution	4mil（code 39） 7mil（QR）
Depth of Field	4mil code39 Near 3.5cm Far 18cm 7mil QR Near 5cm Far9cm

Communication

Radio	2.4G Wireless
Wireless Coverage	2.4G: 100M(line of sight)
Interface/ Profile	2.4G:USB Bluetooth: HID, BLE ,SPP
Host Interface supported	USB

Mechanical

Dimension	170mm × 73mm × 102mm (L x W x H)
Weight	200g

Functionality

Operation Mode	Trigger Mode, Presentation Mode, Buffer Mode

Regulatory Approvals

CE, FCC, BSMI, VCCI

Symbologies

1D	Codabar, Code11, Code39, Code32, Interleaved 2 of 5, Industrial 2 of 5, Matrix 2 of 5, Code93, Code128, GS1-128, UPC-A, UPC-E, EAN 8, EAN 13, GS1 DataBar (RSS14), GS1 DataBar Limited, GS1 DataBar Expanded, etc
2D	PDF417, Micro PDF417, QR Code, Micro QR, Data Matrix, Aztec Code
Data Formatting	Prefix, Suffix, Code ID

Electrical

Operation Voltage	DC 5V
Current Consumption	Operation mode:＜250mA Standby mode:＜1mA
Indicator	Buzzer LED light
Battery Type	Lithium-ion
Battery Capacity	2600mAh 18650 battery
Battery Charging time	Fully charged in 6 hours
Operating Time	Over 16 hours

Environmental

Mechanical Shock	1.5m onto concrete (scanner only)
Operating Temperature	-10°C to 50°C
Storage Temperature	-20°C to 60°C
Relative Humidity	5% to 95% non-condensing
IP Rating	IP54

Package Contents

MS838B scanner
2.4G Dongle
USB Charging Cable

Headquarters
Taipei, Taiwan
http://www.ute.com e-mail: info@hq.ute.com

unitech America
Los Angeles
http://us.ute.com e-mail: info@us.ute.com
http://can.ute.com info@can.ute.com
Mexico
http://latin.ute.com e-mail: info@latin.ute.com

unitech Asia Pacific & Middle East
Taipei
http://apac.ute.com info@apac.ute.com / info@india.ute.com
http://mideast.ute.com info@mideast.ute.com

unitech Europe
Tilburg / Netherlands
http://eu.ute.com e-mail: info@eu.ute.com

unitech Japan
Tokyo
http://jp.ute.com e-mail: info@jp.ute.com

unitech Greater China
Beijing, Shanghai, Guang Zhou, Xiamen
http://cn.ute.com info@cn.ute.com
Taipei http://tw.ute.com info@tw.ute.com

Specifications subject to change without notice. Copyright 2021 unitech Electronics Co., Ltd. All rights reserved. unitech is a registered trademark of unitech Electronics Co., Ltd.
All product and company names are trademarks, service marks, or registered trademarks of their respective owners.

www.ute.com
09/21 Rev.B