

AXIS T91D62 Telescopic Parapet Mount

Parapet installation with telescopic flexibility

AXIS T91D62 Telescopic Parapet Mount is made for parapet and wall installations when the requirement is to place the camera further out from the wall. To compensate for different parapet thicknesses or obstructive elements on the facade of the building, the arm length is adjustable. Its ability to swivel 180 degrees on its own axis, allows for easy and safe mounting/maintenance of the camera from a rooftop. The mount is intended for outdoor fixed and PTZ dome cameras supporting 1.5" NPS thread. A retrofit mounting bracket (optional accessory) makes it possible to reuse holes drilled for Pelco's PTZ dome parapet mount.

- > **Adjustable length, telescopic arm**
- > **Swivel - easy to install and maintain**
- > **Corrosion protected**
- > **Installation flexibility: parapet and wall**



AXIS T91D62 Telescopic Parapet Mount

General			
Casing	NEMA 4X- and IK10-rated impact resistant aluminum mount Color: White NCS S 1002-B		IEC 62262 IK10 NEMA 250 Type 4X* EN 50581 *Corrosion protection
Cable routing	Back: Cable hole Side: Cable conduit holes M25 3/4"	Dimensions	Collapsed arm: 1007 x 783 mm (39.6 x 30.1 in) Expanded arm: 1007 x 1033 mm (39.6 x 40.7 in)
Maximum load	10 kg (22 lb)	Weight	5.9 kg (13 lb)
Mounting option	Parapet and wall	Included accessories	Installation Guide Pull-string
Supported products	AXIS M30 Series (requires AXIS T94F01D Pendant Kit) AXIS P32 Series (requires AXIS T94T01D/T94K01D Pendant Kits) AXIS P33 Series (requires AXIS T94T01D/T94K01D Pendant Kits) AXIS P56 Series (requires AXIS T94A01D Pendant Kit) AXIS Q35-V cameras (requires AXIS T94K01D Pendant Kit) AXIS Q35-VE cameras (requires AXIS T94M01D Pendant Kit) AXIS Q37 Series (requires AXIS T94A01D Pendant Kit) AXIS Q60 Series (requires AXIS T94A01D Pendant Kit) AXIS Q61 Series (requires AXIS T94A01D Pendant Kit)	Optional accessories	AXIS T91D62 Adapter Mounting Bracket AXIS ACI Conduit Adapters AXIS T91B52 Extension Pipes 30/100 cm (0.98/3.2 ft) AXIS Bird Control Spike Network Cable Coupler IP66 For more accessories, see www.axis.com
Environment	Indoor Outdoor	Warranty	3-year warranty, see axis.com/warranty
Approvals	IEC/EN/UL 60950-1 IEC/EN/UL 60950-22	Environmental responsibility: axis.com/environmental-responsibility	