



# Einhell

## EXPERT

Rotary Hammer

**TE-RH 38 3F**

**Item No.: 4257959**

Ident No.: 21011

Bar Code: 4006825663884

The rotary hammer TE-RH 38 3F with pneumatic hammer mechanism is a high-quality and versatile powerhouse for challenging construction, renovation and chiseling jobs. With hammer drilling as well as chiseling with and without chisel fixation this all-rounder is equipped with the three functions for the universal application. The main grip of the rotary hammer is vibration-absorbing and signals the optimal contact pressure via "Press Control" - an important support for low attrition and quick operations, though. The aluminium gear head of the rotary hammer is constructed robustly. Additionally, 2 LEDs inform about the remaining performance and needs of maintenance by attrition of brushes. Delivery in a practical transport case E-Box.

## Features & Benefits

- Hammer drill with pneumatic hammer action for very good drilling
- Robust SDS-Max tool chuck
- 3 functions: hammer drilling, chiseling with and without fixation
- Press-control: visualizes the optimum pressure
- Speed electronics for smooth initial drilling
- Low vibrations thanks to vibration-absorbing main handle
- Soft grip inserts also have a vibration-absorbing impact
- 2 status LEDs: ready for operation and service (brush wear)
- High-grade components for prolonged operation
- Aluminium gear head - light but robust
- Overload slip coupling for safety
- Infinitely adjustable drilling depth stop made of solid metal
- Additional handle with ribs for secure fastening
- Delivered in a practical storage case E-Box M55



## Technical Data

|                                 |                          |
|---------------------------------|--------------------------|
| - Mains supply                  | 220-240 V   50 Hz        |
| - Power                         | 1050 W                   |
| - Idle speed                    | 0-500 min <sup>-1</sup>  |
| - Impact rate                   | 0-4100 min <sup>-1</sup> |
| - Impact power                  | 9 J                      |
| - Tool holder                   | SDS-Max                  |
| - Drilling capacity in concrete | 38 mm                    |

## Logistic Data

|                                      |                    |
|--------------------------------------|--------------------|
| - Product weight                     | 6.62 kg            |
| - Gross weight single packaging      | 9.82 kg            |
| - Dimensions single packaging        | 549 x 408 x 146 mm |
| - Pieces per export carton           | 2 Pieces           |
| - Gross weight export carton         | 19 kg              |
| - Dimensions export carton           | 420 x 565 x 310 mm |
| - Container quantity (20"/40"/40"HC) | 720   1500   1800  |

