



19" 1U Rack Mount 9-Output Power Distribution Unit (PDU)

EU CEE 7/3 Outlets, Built-in 2 m Power Cord with EU CEE 7/7 Plug, 16 A, On/Off Switch, Horizontal Mount, Aluminum, Black

Part No.: **715133**

EAN-13: 0766623715133 | UPC: 766623715133

Rack mount 9-way 19" power strip - power up to nine devices in your network

Plug your networking, telecom, surveillance, AV or other electronics into this 9-outlet 19" PDU from Intellinet Network Solutions. It is compatible with standard electrical equipment and features nine EU Type E/F outlets in a durable black aluminum housing. This PDU mounts in 1U of space in 19-inch racks. The illuminated on/off switch provides one-touch control over all connected devices and has a protective hinged cover to prevent accidental shutdown.

Features:

- 9-way single-phase PDU for electrical equipment, ideal for networking, telecom, security and audio/video
- Built-in 2 m power cord with EU CEE 7/7 (Type E/F) plug
- Illuminated two-pole on/off safety switch with protective cover to prevent accidental shutdown
- Sockets with increased touch protection through contact shutters
- Horizontal 1U 19" rack-mount installation
- Angled outlet orientation
- Durable aluminum construction
- Grounding point to protect equipment from external electrical surges
- Bracket installation style: frontal
- For indoor use only
- Three-year warranty

Specifications:

For more information on Intellinet products, consult your local dealer or visit www.intellinet-network.com.

All names of products or services mentioned herein are trademarks or registered trademarks of their respective owners. Distribution and reproduction of this document, and use and disclosure of the contents herein, are prohibited unless specifically authorized.

Standards and Certifications

- CE
- RoHS
- REACH
- IEC 60297
- IEC 60884

Electrical

- AC input: 220.0 - 250.0 V; 50 - 60 Hz
- Operating voltage: 230.0 V
- Plug standard: EU CEE 7/7 (Type E/F); IEC 60884
- Socket/outlet standard: EU CEE 7/3 (Type F); IEC 60884
- Maximum load: 4,000.0 W
- Overload protection: 16.0 A maximum load current

Physical

- Dimensions (L x W x H): 45 x 483 x 45 mm
- 1U rack mount
- Cable length: 2 m
- Cable type: H05VV-F 3G 1.5 mm²
- Socket angle: 35°
- Net weight: 800 g
- Gross weight: 900 g
- Housing: aluminum

Package Contents

- 19" 1U Rack Mount 9-Output Power Distribution Unit (PDU)

This product is part of a group; the complete list of variations follows:

- #714914 - 1U 6-Way with On/Off Switch
- #711432 - 1.5U 6-Way with Double Air Switch
- #713962 - 1.5U 6-Way with On/Off Switch and Surge Protection
- #715140 - 1U 7-Way with Surge Protection
- #714006 - 1.5U 7-Way with Surge Protection
- #714037 - 1U 8-Way
- #715126 - 1U 8-Way with On/Off Switch
- #713986 - 1U 8-Way with On/Off Switch and Overload Protection
- #715133 - 1U 9-Way with On/Off Switch
- #714044 - Vertical Rack Mount 12-Way with On/Off Switch and Overload Protection
- #711449 - Vertical Rack Mount 12-Way with Single Air Switch
- #714051 - 2U 15-Way with Double Air Switch

