

Product Highlights

Easy Expansion

Easily add 4 x USB 3.0 ports to any Windows and macOS computers, Chromebooks and iPad Pro with a spare USB-C port. Simply plug in, no need to install additional software

Ultra-Fast USB 3.0

SuperSpeed USB 3.0 technology allows you to transfer files up to 10 times faster than with USB 2.0

Fast Charge Port

One USB 3.0 port with Quick Charge BC 1.2 support allows you to charge devices faster



DUB-2340

USB-C to 4-Port USB 3.0 Hub with Power Delivery


Features

Versatile and Convenient

- Four USB 3.0 SuperSpeed 5 Gbps ports
- One USB 3.0 port supports Quick Charge BC 1.2
- One USB 3.0 Type-C port with data sync and power delivery of up to 60 W (20 V @ 3 A)⁴
- Simply plug-and-play, no software required
- Compact design
- Compatible with Windows and macOS computers, Chromebooks and iPad Pro

The DUB-2340 USB-C to 4-Port USB 3.0 Hub with Power Delivery instantly adds four USB 3.0 ports, including one with support for Quick Charge BC 1.2 and a USB-C port with charging ability to your Windows and macOS computers, Chromebooks and iPad Pro. Just plug the DUB-2340 into an available USB-C port, and you're ready to connect up to four USB devices and charge your device faster, as well as sync and charge one USB-C device, meaning that you don't have to give up that USB-C port this hub is connected to.

Hardware Overview



DUB-2340 USB-C to 4-Port USB 3.0 Hub with Power Delivery

Technical Specifications

Connectivity

Interfaces	• One USB Type-C connector • Three USB 3.0 Type-A ports • One USB 3.0 Type-A port with Fast Charge mode support • One USB Type-C/PD 3.0 port
LEDs	• Power (per device) • Solid green - power is on

General

Standards	• USB 3.0 • USB 2.0 • USB 1.1
Data rate	• Up to 5 Gbps
System requirements	• Available USB Type-C port • Windows 7/8/8.1/10, macOS (OS X 10.8 and above) • Chromebook, iPad Pro

Physical

Dimensions (W x H x D)	• 118 x 35 x 13 mm
Weight	• 70 g
Power	• From computer (USB bus powered)
Supplied charging voltage/current	• 20 V / 3 A (PD 3.0) • Max. 1.5 A for Battery Charging 1.2 compliant port • 0.5 A for standard ports
Temperature	• Operating: 0 to 45 °C • Storage: -10 to 70 °C
Humidity	• Operating: up to 85% non-condensing • Storage: up to 85% non-condensing
Certifications	• CE

¹ Please make sure that the USB Type-C port of your laptop supports PD 3.0.



For more information: eu.dlink.com

D-Link (Deutschland) GmbH, Schwalbacher Strasse 74, 65760 Eschborn, Germany
D-Link (Europe) Ltd, Artemis Building, Odyssey Business Park, West End Road, South Ruislip HA4 6QE, United Kingdom
Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners. ©2019 D-Link Corporation. All rights reserved. E&OE.
Updated April 2022

D-Link[®]
Building Networks for People