# PowerWalker Basic VI 650-1000 SB Series

- Human Interface Device (HID) compatible USB connection (no additional drivers needed)
- Compact and lightweight
- Reduced environmental impact: no CD, no USB cable in the box
- Equipped with Boost and Buck AVR to stabilize output voltage
- Cold (DC) Start Function
- Available with outlets type E, F and G

2018 PREMIERE

No CD

No USB cable

Reduced Environmental Impact

HID Support

The PowerWalker Basic VI 650/850/1000 SB series is designed to answer the essential market needs. This line interactive UPS will protect your load from power failures and voltage disturbances, while remaining affordable and compact. It is equipped with a USB port with HID support allowing easy and immediate communication with any O/S.

The managing software PowerWalker PowerMaster is available for download from our website: www.powermaster.powerwalker.com.





VI 650/850 SB outlets: Type F, Type E and Type G



VI 1000 SB outlets: Type F, Type E

| MODEL | VI 650 SB | VI 850 SB | VI 1000 SB |
|---|---|---|---|
| Item Number (Type F outlet) | 10121066 | 10121067 | 10121068 |
| Item Number (Type E outlet) | 10121069 | 10121070 | 10121071 |
| Item Number (Type G outlet) | 10121096 | 10121097 | 10121098 |
| Power (kVA) | 650VA | 850VA | 1000VA |
| Power (kW) | 360W | 480W | 600W |
| **INPUT** | | | |
| Voltage | 162-290 VAC | | |
| Plug | Standard: Type F or British Type G | | |
| Frequency Range | Auto-sensing at 50Hz 60Hz | | |
| **OUTPUT** | | | |
| Voltage | 230 VAC ±10% | | |
| Freqency Range | 50Hz or 60Hz +/-1Hz | | |
| Waveform | Pulse Width Modulated Alternating Voltage | | |
| Switching Time | Typical 4ms | | |
| Outlets | 2 x Type F or 2x Type E (French) or 2x Type G (British) | | 3 x Type F or 3x Type E or 3x Type G |
| **EFFICIENCY** | | | |
| AC Mode | 95,3% | 96,4% | 96,5% |
| **COMMUNICATION** | | | |
| Port | USB Port with HID support (cable not provided) | | |
| Software | PowerWalker PowerMaster available on website | | |
| **BATTERY** | | | |
| Amount | 1x5Ah/12V | 1x6Ah/12V | 2x5Ah/12V |
| Charging Time | 8h to 90% | | |
| Half-Load backup time | 4,5min | | 7min |



02/02/2018