



FCS-4203 Version: 1

GEMINI Zoom Dome IP Network Camera, 2-Megapixel, H.265, 4.3X Optical Zoom, two-way audio, IR LEDs, 802.3af PoE, Vandalproof, Indoor/Outdoor

The LevelOne FCS-4203 Fixed Dome Outdoor Camera offers a highly reliable, cost-effective outdoor IP surveillance solution in a low-profile dome mounted casing, which is rated at IP66 and able to withstand outdoor operating conditions such as rain, snow, extreme heat, dust and humidity. The FCS-4203 offers 2-Megapixel resolution, and with 802.3af standard PoE, can use a single Cat.5 cable to run both power and data, making deployments easy and flexible. The dome mounting prevents malicious tampering with the camera, making it a secure and smart choice for all outdoor installations.

Key Features

- 2-Megapixel (1920 x 1080) high-definition resolution
- Video compression: H.264, H.265, MJPEG
- Supports 4.3X optical zoom
- Built-in infrared LEDs for night viewing up to 30m
- Vandal-proof IK10-rated housing
- Power support: PoE (IEEE 802.3af)
- Built-in Micro SD/SDHC card slot for local storage

Specifications

System Specifications

Standards & Protocols:

TCP/IP (IPv4), UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour

Image Sensor:

1/2.8" Progressive Scan CMOS

Lens:

2.8 mm to 12 mm @ $f/1.4$, motorized lens

Port:

10/100Mbps (100Base-T) RJ45 Ethernet interface

Power Connector

Audio:In/Out

I/O terminal block (1 DI/1 DO)

1 x MicroSDHC/ MicroSDXC card slot

**Button/Knob:**

Reset Button

Indicator:

Power

IR Cut Filter:

Yes

IR LED:

Up to 30m

Shutter Time:

1/3 s to 1/100,000 s

Angle of View:

Horizontal field of view: 105°to 35°

Pan/Tilt/Zoom:

2.8-12 mm motorized lens

Video Compression:

H.265/H.264/MJPEG

Resolution:

50Hz: 25fps (1920 × 1080, 1280 × 960, 1280×720)

60Hz: 30fps (1920 × 1080, 1280 × 960, 1280×720)

Output Video Format:

AVI

Audio Compression:

G.711/G.722.1/G.726/MP2L2, 64 Kbps (G.711)/16 Kbps

(G.722.1)/16 Kbps (G.726)/32 to 128 Kbps (MP2L2)

Power Input:

12V DC±10%, PoE (802.3af)

Power Consumption:

12 VDC, 0.75A, max. 9.5W

PoE0.3A to 0.1A, max. 11W

Data Rate:

2Kbps~16Mbps

Storage Capacity:

Support Micro SD/SDHC/SDXC card with ANR (up to 128G)

Features

General:

Rotate Mode, Saturation, Brightness, Contrast, Sharpness adjustable by client software or web browser

PoE:

PoE (802.3af Class3)

Security:

One-key reset, Anti-Flicker, heartbeat, mirror, password protection, privacy mask, Watermark, IP address filtering, Anonymous access

Video:

Adjustable image size, quality and bit rate, 3D Digital Noise Reduction, 120 dB Wide Dynamic Range, Triple Video Streams Configurable brightness, sharpness, contrast, saturation, white balance and exposure

- Motion detection

Audio:

G.711/G.722.1/G.726/MP2L2

Performance

Number of Clients:

16

Frame Rate (fps):

First Stream:

50Hz: 25fps (1920 × 1080, 1280 × 960, 1280×720)

60Hz: 30fps (1920 × 1080, 1280 × 960, 1280×720)

Sub Stream:

50Hz: 25fps (640 × 480, 640 × 360, 320 × 240)

60Hz: 30fps (640 × 480, 640 × 360, 320 × 240)

Third Stream:

50Hz: 25fps (1920 × 1080, 1280×720, 640 × 360, 352 × 288)

60Hz: 30fps (1920 × 1080, 1280×720, 640 × 360, 352 × 240)

Minimum illumination:

Color: 0.005 Lux @ (F1.2, AGC ON), 0 Lux with IR

B/W: 0.0068 Lux @ (F1.4, AGC ON), 0 Lux with IR

Environment

Operating Temperature (°C):

-30° C to 60° C (-22° F to 140° F)

Operating Humidity (Non-condensing):

Humidity 95% or less (non-condensing)

Physical Specifications

Dimensions (W x D x H mm):

153.4 × 133.1 mm (6.04" × 5.24")

Weight (g):

1287 g (2.84 lb.)

Color:

White

Approval and Compliance

EMI/EMS:

CE/FCC

Safety:

IK10

Environmental Test:

IP67

Others:

ONVIF (Profile S, Profile G), PSIA, CGI, ISAPI, ISO-9001 certified factory

RoHS

Others

Supported Browsers:

Internet Explorer 9.0 or above

Order Information

FCS-4203

Package Contents

FCS-4203

Resource CD (User Manual, Utility, 64-CH Monitoring Software)

Screw Kit

Optional Accessory



CAS-7342

Pendant Mount Bracket



CAS-7343

Wall Mount Bracket



CAS-7344

Pole Mount Bracket, Clamping Range 2.6"-5"



CAS-7345

Corner Mount Bracket

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.