



TP-Link AC1350 Wireless MU-MIMO Gigabit Ceiling Mount Access Point

Brand : TP-Link

Product code: EAP223

Product name : AC1350 Wireless MU-MIMO Gigabit Ceiling Mount Access Point

- Fast Dual-Band Wi-Fi: Simultaneous 450 Mbps on 2.4 GHz and 867 Mbps on 5 GHz totals 1317 Mbps Wi-Fi speeds.†
 - Integrated into Omada SDN: Zero-Touch Provisioning (ZTP)‡, Centralized Cloud Management, and Intelligent Monitoring
 - Centralized Management: Cloud access and Omada app for ultra convenience and easy management
 - Seamless Roaming: Even video streams and voice calls are unaffected as users move between locations.*
 - PoE Support: Support both standard 802.3af/at and Passive PoE (PoE adapter is not included) for flexible installations
 - Secure Guest Network: Along with multiple authentication options (SMS/Facebook Wi-Fi/ Voucher, etc.) and abundant wireless security technologies
 - Advanced Wireless Tech: Optimize network performance with MU-MIMO, Band Steering, Airtime Fairness and Beamforming technologies
- AC1350 Wireless MU-MIMO Gigabit Ceiling Mount Access Point



Features		Power	
2.4 GHz *	✓	Power over Ethernet (PoE) *	✓
5 GHz *	✓	Power over Ethernet (PoE) type supported	Active PoE, Passive PoE
6 GHz *	✗	Output voltage	48 V
Maximum data transfer rate *	867 Mbit/s	Power consumption (typical)	9.7 W
Maximum data transfer rate (2.4 GHz)	450 Mbit/s	Design	
Maximum data transfer rate (5 GHz)	867 Mbit/s	Placement *	Ceiling, Wall
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n	Product colour *	White
Automatic channel selection	✓	Reset button	✓
Automatic channel scanning	✓	LED indicators	Power
MIMO	✓	Certification	CE, FCC, RoHS
MIMO type	Multi User MIMO	Antenna	
Wi-Fi Multimedia (WMM)/(WME)	✓	Antenna type *	Internal
VLAN support	✓	Antenna direction type	Omni-directional
Rate limiting	✓	Antennas quantity	3
Wireless isolation	✓	Performance	
Band steering	✓	Compatible operating systems	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux
Quality of Service (QoS) support	✓	Weight & dimensions	
Transmitting power (CE)	20, 23 dBm	Width	205.5 mm
Transmitting power (FCC)	24, 22 dBm	Depth	181.5 mm
Security		Height	37.1 mm
Security algorithms *	SSID	Packaging content	
MAC address filtering	✓	Number of products included	1 pc(s)
Number of SSID supported	15	Cables included	AC
Management features		Mounting kit	✓
Web-based management	✓	Quick start guide	✓
Syslog	✓	Operational conditions	
Management platform	Omada	Operating relative humidity (H-H)	10 - 90%
Ports & interfaces		Operating temperature (T-T)	0 - 40 °C
Ethernet LAN (RJ-45) ports *	1		

Operational conditions

Storage temperature (T-T)	-40 - 70 °C
Storage relative humidity (H-H)	5 - 90%



4895252500509



0840030704277



840030704277

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 09-MAY-2024. Prints or copies of Information are only valid on the printed Publication date