

Twisted Pair Patch Cord - Category 6_A Class E_A - S/FTP



✓ LSZH (Low Smoke Zero Halogen)

✓ Yellow colored plug for CAT 6_A

✓ Kink prot., strain relief, latch prot.

✓ various lengths and colors available

Abstract

CAT 6_A Class E_A, S/FTP, Twisted Pair Patch Cord, Cu, LSZH, AWG 26/7, various lengths and colors available

Features

- 2x RJ45 (8P8C) connectors
- Boots with kink protection, strain relief and latch protection
- Length marking on boot
- Conductor: Cu (Copper)
- Shielding: S/FTP (complete braid shielding, pairs foil shielded)
- Structure: 4x 2 AWG 26/7, twisted pair
- Sheath: LSZH (Low Smoke Zero Halogen)
- Supports PoE, PoE+, PoE++ (IEEE 802.3af; 3at; bt)

Product Overview

The DIGITUS Category 6_A Class E_A patch cords are manufactured and tested to the ISO/IEC 11801 and DIN EN 50173 Category 6_A specifications. They will guarantee the installed cabling system is compliant with the ISO & EN channel specification requirements and will provide optimum performance levels of DIGITUS Category 6_A cabling. The performance is tested up to 500 MHz inclusive performance characteristics such as near end cross talk ("NEXT").

DIGITUS patch cords are designed and produced to fulfill the highest requirements of various application areas in full volume.

Each cable is fitted with a molded boot which comes with kink protection and strain relief.

Furthermore the boot is equipped with a latch protection that prevents the latching lever against breaking.

You can easily identify the Category 6_A, because of the transparent yellow colored connector.

Performance- and Specification Overview


Conductor	Stranded AWG 26/7 bare copper, 0.148 ± 0.005 mm
Outer sheath	LSZH (Low Smoke Zero Halogen)
Overall diameter	5.8 mm $\pm$ 0.30 mm
Bending radius	15x OD
RJ45 connector	3 μ nominal gold flash over 60 μ nickel undercoat contact pins
Color code	Orange x White, Green x White, Blue x White, Brown x White
Wiring standard	EIA/TIA 568B
Pin assignment	1:1
Durability	750 insertion cycles
Contact resistance	30 m Ω maximum
Resistance unbalance	3% maximum
Dielectric strength	2500 VDC for 3 seconds
Uninsulated resistance	150 M Ω /km minimum
Operating temperature	-20 °C up to +60 °
NVP	76%
Flame retardancy	IEC 60332-1
Smoke emission	IEC 61034
Typical applications	IEEE 802.3: 10BASE-T; 100BASE-T; 1000BASE-T; 10GBASE-T
Norms	ISO/IEC 11801-1; EN-50173; ANSI/TIA 568-C.2; EN 60603-7-51
Colors	Various colors available on request
Marking	Brand name, cable length and cable information

Transmission Properties

Freq.	Insertion Loss	NEXT	RL	ACR-F	PS NEXT	PS ACRF
MHz	dB	dB	dB	dB	dB	dB
1.00	4.00	65.00	19.00	63.30	62.00	60.30
10.00	6.50	56.60	19.00	43.30	54.00	40.30
20.00	9.20	51.60	17.50	37.20	49.00	34.20
25.00	10.20	50.00	17.00	35.30	47.30	32.30
62.50	16.40	43.40	14.00	27.30	40.60	24.30
100.00	20.90	39.90	12.00	23.30	37.10	20.30
200.00	30.10	34.80	9.00	17.20	31.90	14.20
350.00	40.60	30.30	6.60	12.40	27.60	9.40
500.00	49.30	27.90	6.00	9.30	24.80	6.30

The results of the chart above are typical for Category 6_A, Class E_A patch cords 2 m, 5 m up to 10 m length

Product Number Information



Order information and Length Tolerances

Article No	#Length (m)	Tolerance (mm)
DK-1644-A-0025*	0.25	+20/-6
DK-1644-A-005*	0.5	+20/-10
DK-1644-A-010*	1.0	+/-20
DK-1644-A-015*	1.5	+/-30
DK-1644-A-020*	2.0	+/-40
DK-1644-A-025	2.5	+/-50
DK-1644-A-030*	3.0	+/-60
DK-1644-A-040	4.0	+/-70
DK-1644-A-050*	5.0	+/-110
DK-1644-A-070*	7.0	+/-140
DK-1644-A-100*	10	+/-200
DK-1644-A-150*	15	+/-310
DK-1644-A-200*	20	+/- 470
DK-1644-A-250*	20	+/- 490
DK-1644-A-300*	30	+/-510
DK-1644-A-500*	50	+/-560
*available in different colors see below		# The cable length is measured from plug A to plug B
DK-1644-30/Y=Yellow other colors B= Blue; BL=Black; G=Green; R=Red; MG=Magenta; VI=Violet		

Technical Drawing

