



GEU-0522 Version: 1

5-Port Gigabit Switch

The LevelOne GEU-0522 is a wire-speed, non-blocking networking device that provides 5 ports 10/100/1000Mbps Ethernet connections. All ports support auto-negotiation and auto-MDI/MDIX sensing, eliminating the need for crossover cables or Uplink Ports. Each port can be used as general network port or as connecting port into a router, server, hub or another network switch.

Key Features

- 1000Mbps full-duplex, 10/100Mbps full/half-duplex, auto-negotiation, auto-MDI/MDIX
- Supports 4K MAC address auto-learning and auto-aging
- Quick and easy installation
- Minimize carbon footprint with advanced energy efficient technology (IEEE 802.3az)

Specifications

System Specifications

Standards & Protocols:

IEEE802.3(10BASE-T)

IEEE802.3u(100BASE-T)

IEEE802.3ab(1000BASE-T)

IEEE802.3az Energy Efficient Ethernet

Buffer Memory:

64k

Connectors and Cabling:

5 x 10/100/1000Base-T RJ-45 Port

Indicator:

Power, LINK/ACT

Transmission Method:

Store- forward

Power Input:

5V/0.6A

Backplane (Gbps):

10Gbps

MAC Address Table:

1K

Data Transfer Rate:

10/100/1000Mbps

Performance

Packet Forwarding Rate:

10Mbps:14880pps

100Mbps:148810pps

1000Mbps:1488100pps

Jumbo Frame (K):

9k

Switching Capacity:

10Gbps

Environment

Temperature (°C):

Operating: 0°C ~ 50°C

Storage: - 40°C ~ 70°C

Humidity (Non-condensing):

Operate:10 ~ 90%

Storage:5 ~ 90%

Physical Specifications

Dimensions (W x D x H mm):

89*86*23mm

Weight (g):

71.4g


Approval and Compliance

EMI/EMS:

CE

FCC

Diagram



Order Information

GEU-0522

Package Contents

GEU-0522
Power Adapter
Quick Installation Guide

No liability or responsibility for any errors or omissions in the content.
Specifications are subject to change without notice.
All mentioned brand names are registered trademarks and property of their owners.
Copyright © Digital Data Communications GmbH, Germany. All Rights Reserved.