



IPC 4U-4460-TFT 19" rack with 8,9" Touch TFT display

With its built-in 8,9" Touch TFT display the **4460-TFT** is ideal for servers and workstations in locations where is no space for a separate monitor.

The dust filter in front of the serial 120mm fan in the front prevents dust getting in the case and is removable within a few steps.

A USB 3.0 Type A front connector that is equipped with an adapter to USB 2.0 connector on the mainboard completes the offer.

Specifications

Mainboard	Mini ITX, µATX, ATX, E-ATX
Drive Bays	Max. Mainboard size WxD: 305mm x 330mm, 12" x 13"
	5.25" external: 0
	2,5"/3,5" extern hinten Hot Swap: 0
	3.5" internal: 3*
	2.5" internal: 6**
Front Connectors	USB 3.0: 1
Cooling System	Internal (front): 1x 120mm (serial, incl. filter, Molex)
	Internal (rear): 2x 80mm (optional)
Controls	Power-Button
LED	Power
Power Supply	ATX-PSU, PS2 Mini-redundant-PSU
Material	1.0-1.2mm Steel
Maximum CPU cooler height	125mm
Maximum graphics card length	390mm
Packing Units	Shipping Unit: 1 Piece Pallet: 12 Pieces
Guarantee and Warranty	Case 24 Months Warranty
Article Number	88887317
EAN-Code	4260455646093
Scope of Delivery	Screw set VGA cable
Features	Serial 1x 120mm fan with dust filter 7 perforated slot-brackets USB 3.0 internal as 19Pin block connector 8.9" TFT display resolution max. 1920x1080 USB 9Pin: touch panel mainboard VGA/ Molex/ USB 9Pin

*can vary by using several mounting options
** 4x exclusively up to max. 7mm height

Dimensions and Weight

	Cage	Case	Package
Height	177mm	177mm	275mm
Width	428mm	480mm	555mm
Depth	435mm	499mm	595mm

Weight (net): 8.90kg
Weight (gross): 11.66kg

Power supply

Connector	Quantity	Max. Length
Mainboard 20+4Pin	-	-
P4 12V 4Pin	-	-
P4/EPS 4+4Pin	-	-
P8 12V 8Pin	-	-
PCI-Express 6+2Pin	-	-
PCI-Express 6Pin	-	-
IDE 4Pin	-	-
S-ATA	-	-
Floppy	-	-
RPM sensor cable	-	-
Fan control	-	-
Fan 120mm	-	-

Certification:

