

SMT2200RMI2UC



Intelligent and efficient network power protection from entry level to scaleable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other ...

Includes: CD with software, Documentation CD, Rack mounting hardware, Rack Mounting support rails, USB cable



Technical Specifications

Output

Max Configurable Power (Watts)	1.98kWatts / 2.2kVA
Output Voltage Note	Configurable for 220 : 230 or 240 nominal output voltage
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	50/60Hz +/- 3 Hz
Other Output Voltages	220, 240
Topology	Line Interactive
Waveform type	Sine wave
Transfer Time	6ms typical : 10ms maximum

Input

Input frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input voltage range for main operations	160 - 286V
Input voltage adjustable range for mains operation	151 - 302V
Number of Power Cords	1
Other Input Voltages	220, 240

Batteries & Runtime

Battery type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	3hour(s)
Replacement Battery	RBC43 ↗
Expected Battery Life (years)	3 - 5
RBC Quantity	1
Battery Volt-Amp-Hour Capacity	509
Runtime	View Runtime Graph View Runtime Chart

Communications & Management

Interface Port(s)	RJ-45 Serial, SmartSlot, USB
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Available SmartSlot™ Interface Quantity	1

Surge Protection and Filtering

Surge energy rating	375Joules
---------------------	-----------

Physical

Maximum Height	86MM, 8.6CM
Maximum Width	432MM, 43.2CM
Maximum Depth	683MM, 68.3CM
Net Weight	42.31KG
Shipping weight	49.73KG
Shipping Height	254MM, 25.4CM
Shipping Width	600MM, 60.0CM
Shipping Depth	980MM, 98.0CM
Units per Pallet	8.0

Environmental

Operating Temperature	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000meters
Audible noise at 1 meter from surface of unit	55.0dBA
Online thermal dissipation	215.0BTU/hr

Conformance

Approvals	CE, EAC, EN 60950, EN/IEC 62040-1, EN/IEC 62040-2, GS Mark, IRAM, RCM, VDE, WEEE
Standard warranty	3 years repair or replace (excluding battery) and 2 year for battery

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains SVHCs