Product datasheet

Specifications



APC Smart-UPS On-Line SRT Battery Pack for 8/10kVA Extended runtime model 192V

SRT192BP2

EAN Code: 0731304292746

Main

Product or component type	External battery pack
Number of rack unit	3U
Battery type	Lead-acid battery
Provided equipment	Documentation CD Installation guide Warranty card
Range of product	Smart-UPS Battery Systems
Replacement battery	APCRBC140

Batteries & Runtime

Number of battery free slots	0
Number of battery filled slots	0
Device mounting	Stand alone battery stack
Battery voltage	+/- 192 V
Number of battery replacement quantity	2

Physical

Colour	Black
Height	432 mm
Width	130 mm
Depth	682.7 mm
Net weight	91 kg
Mounting mode	Rack-mounted with kit

Output

Battery capacity	10 Ah

Environmental

Ambient air temperature for operation	0…40 °C
Operating altitude	0...10000 ft
Relative humidity	0…95 % non-condensing
Ambient air temperature for storage	-15…45 °C
Storage altitude	0…15240 m

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Storage Relative Humidity	0…95 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	42.000 cm
Package 1 Width	100.000 cm
Package 1 Length	60.000 cm
Package 1 Weight	101.500 kg

Logistical informations

Country of origin	VN

Contractual warranty

Warranty (in months)	24

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**465 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**376 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**25 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**29 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**354 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**36 kg CO2 eq.**

Use Better

Materials and Substances

Average percentage of recycled plastic content	**15 %**
Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
SCIP Number	**488c31fb-3af8-42cf-9558-1362d000a07e**
EU RoHS Directive	**Compliant**
REACh Regulation	**Reference contains Substances of Very High Concern above the threshold**

Use Again

Repack and remanufacture

Recyclability potential, in %	**48**
End of life manual availability	**End of Life Information**
Removable battery	**User replaceable**
Take-back	**No**
WEEE Label	**The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins**

Image of product / Alternate images

Alternative



