



D-Link DSR-250V2 wireless router Gigabit Ethernet Black

Brand : D-Link
Product code: DSR-250V2
Product name : DSR-250V2

- Automatic failover to another link from available ISP when primary line is lost
- Support 1 x GE WAN, 3 x GE LAN, 1 GE Configurable LAN/WAN and 1 x USB 3.0 port
- 900/200 Mbps firewall/VPN throughput, 50,000 Concurrent Sessions, and 50/20 IPsec/SSL VPN Tunnels
- Advanced routing, VLAN and IPsec/PPTP/L2TP/OpenVPN VPN Server/Client
- Value-added office utilities to reduce OpEx/CAPEX
- Traffic load balancing and Avoid complicated maintenance issues

5-Gigabit Port VPN Router DSR-250v2

D-Link DSR-250V2. Top Wi-Fi standard: 802.11g, Wi-Fi standards: 802.11g. Ethernet LAN interface type: Gigabit Ethernet, Ethernet LAN data rates: 10,100,1000 Mbit/s. Security algorithms: 3DES, 128-bit RC4, AES, SNMP, SNMPv2, SNMPv3. Routing protocols: OSPF, OSPFv3, RIP-1, RIP-2. Product type: Desktop/pole router, Product colour: Black



WAN connection		Protocols	
Ethernet WAN *	✓	DHCP client	✓
SIM card slot *	✗	DHCP server	✓
Wireless LAN features		Routing protocols	OSPF, OSPFv3, RIP-1, RIP-2
Top Wi-Fi standard *	802.11g	Design	
Wi-Fi standards	802.11g	Product colour	Black
Network		Product type *	Desktop/pole router
Ethernet LAN *	✓	Antenna	
Ethernet LAN interface type *	Gigabit Ethernet	Antenna design *	Internal
Ethernet LAN data rates	10,100,1000 Mbit/s	Features	
Static route	✓	Mean time between failures (MTBF)	123015785 h
VPN tunnels quantity	75	Power	
VPN Passthrough	✓	Power source type *	DC
Ports & interfaces		Power consumption (typical)	14.4 W
Ethernet LAN (RJ-45) ports *	5	Operational conditions	
USB port *	✓	Operating temperature (T-T)	0 - 40 °C
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Storage temperature (T-T)	20 - 70 °C
DC-in jack	✓	Operating relative humidity (H-H)	5 - 95%
Management features		Weight & dimensions	
Web-based management	✓	Width	120 mm
Security		Depth	190 mm
Security algorithms	3DES, 128-bit RC4, AES, SNMP, SNMPv2, SNMPv3	Height	38 mm
Firewall	✓		



0790069461828



790069461828

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 08-MAY-2024. Prints or copies of Information are only valid on the printed Publication date